

GFE88CSC (Canopied)



Engine	Alternator	Model		Power factor	Emissions	
Cummins 4BTA3.9-G11	Stamford UCI224G	GFE88CSC (Canopied)		Factor $\Phi = 0.8$	N/A	
50Hz	1500rpm	3-Phase				
Ratings	Prime Power		Standby Power		Rated current	Fuel consumption
Voltage	(PRP)		(ESP)		Amps	@100% load
(V)	kWe	kVA	kWe	kVA	(A)	L/h
400	64	80	72	88	115.5	20

Ratings All three phase generator sets are rated at 0.8 power factor.
All single-phase generator sets are rated at unity or 1.0 power factor.

Prime output This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby output This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.

The above ratings are in accordance with ISO8528-1 and ISO3046-1. Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity.

Engine

Cummins 4BTA3.9-G11

		Units	
General performance	Frequency	Hz	50
	Engine speed	r/min	1500
	Number of cylinders / arrangement		4 cyl / vertical in-line
	Displacement	Litres	3.9 L
	Aspiration		Turbocharged
	Combustion system		Direct injection
	Governor type		Electronic
	Bore / stroke	mm	102 x 120
	Starter Motor / Charge Alternator (V dc)		24 V DC
	Engine power (gross)	kWm	Prime: 80 Standby: 88
Cooling system		Water cooled	
Rotation		Anti-clockwise viewed on flywheel	
Fuel system	Fuel consumption at 110% Prime Power	Litres/hour	22
	Fuel consumption at 100% Prime Power	Litres/hour	20
	Fuel consumption at 75% Prime Power	Litres/hour	15
	Fuel consumption at 50% Prime Power	Litres/hour	10
	12 hour fuel tank capacity	Litres	160
Air system	Air inlet		Mounted air filter
	Air filter type		Dry
Fuel and fuel system	Electronically governed		YES
	Rotary type pump		YES
	Ecoplus fuel filter		YES
Oil system	Total oil system capacity	Litres	16.4
	Maximum sump capacity	Litres	N/A
	Wet sump with filler and dipstick		YES
	Spin-on oil filter		YES
Cooling system	Total system capacity		
	- With radiator	Litres	N/A
	- Without radiator	Litres	N/A
	Thermostat operation range	°C	up to 40°C
Maximum top tank temperature	°C	N/A	
Electric system	Electrical system voltage	V	24
	Battery		Maintenance-free
	Connecting cables		Included
Available options	Battery charger		Included
	Battery isolator switch		Included
	125 AMP 5 Pin (IP67) Socket Outlet		Excluded

Alternator

Stamford UCI224G

		Units	
General data	Manufacturer / brand		Stamford
	Model		UCI224G
	Coupling / number of bearings		Flexible Disc / Single Bearing
	Phase / Poles		3-Phase / 4-Pole
	Power factor		Cos ϕ = 0.8
	AVR Regulation		Yes
	Voltage Regulation		± 1 %
	Insulation class		H
	Drip proof		IP23
	Excitation		Shunt
	Altitude	m	≤ 1000
	Overspeed	min -1	2250

DSE Controller Summary

Controller model / Deepsea DSE	Standard: DSE4520	Optional: DSE6120	Optional: DSE7310/20	Optional: DSE8610/20
--------------------------------	----------------------	----------------------	-------------------------	-------------------------

Controller photos



Standard supply

•	○	○	○
---	---	---	---

Viewable parameters

Phase voltage	x	3	3	3
Current	Instrumentation	•	•	•
Frequency	•	•	•	•
Active power	○	•	•	•
Reactive power	○	•	•	•
Apparent power	x	•	•	•
Power factor	○	•	•	•
Electric energy metering	x	•	•	•

Generator protection

Abnormal voltage	•	•	•	•
Overcurrent warning	○	•	•	•
Overcurrent protection	•	•	•	•
Over frequency protection	•	•	•	•
Short circuit protection	MCCB / •	MCCB / •	MCCB / •	MCCB / •

Engine figure

Oil pressure	•	•	•	•
Water temperature	•	•	•	•
Fuel meter / fuel sensor	•/○	•/○	•/○	•/○
Speed	•	•	•	•
Battery voltage	•	•	•	•
Elapsed time	•	•	•	•

Engine protection

Low oil pressure warning	x	•	•	•
Low oil pressure protection	•	•	•	•
High temperature warning	○	•	•	•
High temperature protection	•	•	•	•
Overspeed warning	x	•	•	•
Overspeed protection	○	•	•	•
Alternator charger	•	•	•	•

Functions

Remote start	•	•	•	•
AMF (Auto Main Failure)	•	•	•	•
Programmable input	•	•	•	•
Programmable output	•	•	•	•
Expand module	x	○	○	○
Communication function	x	x	RS232 / 484	RS232 / 485
Communication port	USB	USB	RS232 / 484	RS232 / 485
CAN	•	○	•	•
Service indicate	○	○	•	•
Fault history	•	•	•	•
Gen-gen synchronising	x	x	x	•
Gen-mains synchronising (20)	x	x	x	•

Remark: • Standard supply ○ Available as optional × Not available

Enclosure / Canopy

Sound-attenuated or open option

“Ensure a quieter life with our sound attenuation system.”

Features

Extremely rugged and highly corrosion resistant construction

- Unique appearance with high sound absorbing and thermal properties
- 8-12 hours built-in fuel tank integrated into the skid-mount base
- Excellent design and craftsmanship
- Full weatherproof enclosure, suitable for operations in harsh conditions
- Thermo-acoustic installation which can withstand fire, high temperature and severe conditions
- Residential exhaust muffler manufactured from galvanised steel
- High quality polyester powder paint
- Designed on modular principles with interchangeable components permitting on-site repairs



*Image for reference only. Actual product will differ

Easy commissioning and maintenance

- Control panel viewing window with lockable access door for quick, safe and easy monitoring
- Side doors allowing 180° opening for easy accessibility
- Lifting point for easy mobility
- Lube oil drain and radiator drain
- Internally mounted exhaust silencers constructed to withstand rough conditions

Security and safety


- Earth leakage protection
- Secure and lockable access doors for fuel fill and battery
- Fully guarded cooling fan and battery charging alternator
- Emergency stop push button mounted on the enclosure exterior for urgent and safe shutdown
- Efficient management of cooling air to avoid high water temperature

Transportability

- Top access lifting points for crane lifting
- Fork lift pockets for easy moveability

Overall dimensions, weight and noise

Frame type	Dimensions	Weight	Base tank @100% load		Noise level
	(L x W x H) mm	kg	Hours	Litres	dB(A) at 7m
Canopied	2450x1065x1485	TBC	8	160	70.5
Open					



Automatic Transfer Switch

A.T.S - 4 Poles

We offer as an optional accessory, not only a changeover switch but also an integrated mains detection and switch system for your 24 hour power protection. The system enables automatic start-up and operation of the generating set in the event of a mains power failure, overvoltage or loss of a mains automatic retransfer once it comes back.

System advantages

Automatically transfer and re-transfer load from main power to gen-power without operator intervention (both automatic and manual)

ATS Controller (AMF function)

Available from 32 - 4000A

Available in standard, bypass isolation and service-entrance configurations

Configurable in open, closed and programmed transition operating modes

Designed to interface seamlessly with all AMF generators and switchgear

Drip proof IP42 enclosure

Easy installation: wall-mounted and floor standing



*image for illustration purposes only, actual product may differ

Warranty coverage

Generators used with commercial utility source: One (1) year or 1000 hours (whichever occurs first) from date of shipment from the factory or registered start-up date.